



## PROCESSING INSTRUCTIONS

### **KAMBA Floor**

#### **Your anti-slip coating for all floor covering**

Item number 16300 / 16350

##### **Important note:**

During coating and for 24 hours afterwards, ensure that the surface temperature is above 15°C!

Before use, observe the safety instructions on the respective labels!

In our safety box, you will find everything you need for YOUR SLIP RESISTANCE in accordance with DIN 51130:

For the first steps, we recommend that you wear household gloves

1. Removal of all limescale residues:  
Wet the surface with warm water.  
Then clean thoroughly with a floor cleaner and a sponge.  
Rub the surface dry and keep it completely dry for 12 hours  
Pro tip: Avoid direct sunlight and do not apply outdoors if there is a risk of rain when using Kamba Floor
2. Limit the area to be coated with the enclosed adhesive tape.
3. Place the special roller on the roller bracket
4. Shake KAMBA anti-slip vigorously (>2 min.) The quantity is sufficient for approx. 2 m<sup>2</sup>.
5. Pour the required amount into the enclosed coating tray.
6. Dip the special roller into the coating material; roll out any excess material until the roller is evenly saturated and no longer drips.

7. Begin coating. Always work from the center of the surface outwards. First coat the surface evenly and thinly in one direction then, at a 90° angle, spread the already applied material again with the roller; again at a 90° angle (without applying pressure to the roller)  
Pro-Tip: during the last pass without pressure on the roller.
8. Please remove the adhesive tape immediately after coating.
9. Any unused anti-slip coating material can be poured back into the bottle. The bottle is tightly sealed and can be stored at cellar temperature for approx. 3 months.
10. Wash all tools thoroughly with lukewarm water for reuse
11. After 12 hours of drying time, your floor is ready for use again.  
(Optimal conditions: temperature > 20°C and good ventilation!)
12. Mechanical cleaning may only be carried out after 3 days of drying

We are happy to assist you with any problems. Simply send an email to [info@kamba-antirutsch.de](mailto:info@kamba-antirutsch.de)